



CATALYST

COMMERCIAL QUALITY • PROFESSIONAL RESULTS

LAWN CARE BEYOND REEL

A new member of the legendary family is taking lawn care to a whole new level. Available in 20" and 25" models, this machine is not only a precision reel mower; it can also be quickly and easily transformed to perform several other beneficial maintenance functions, including verticutting, aerating, moss removal, de-thatching, and sweeping. It features the same level of high-quality components as the original models, along with additional features and accessories that enhance performance and operator control.



Folding Upper Handle



Self-Propel & Cartridge Engagement Levers



Coated Split Rear Drum Roller with Differential Function



25" Model Available



Commercial Duty Engines

HONDA



GX160

XR3.5



Splined Belt Main Drive



Easy Maintenance Drum & Cartridge Drive



Large Capacity Semi-Enclosed Catcher



Split Grooved or Smooth Front Roller

Thick Steel 7 or 10 Blade Reel with Relief Grind



Quick-Adjust Cutting Heights
0.125 - 1.20in (3-30mm)



SEE BACKSIDE FOR OPTIONAL ACCESSORIES / CARTRIDGES / SPECS >>>



CATALYST

COMMERCIAL QUALITY • PROFESSIONAL RESULTS

OPTIONAL ACCESSORIES & CARTRIDGES



Components / Specifications	20	25
Engine Options	Briggs & Stratton XR3.5 (20") Honda GX160 (20" & 25")	
Drive Engagement Levers	Separate for Propel & Cartridge	
Engine to Frame Drive	Heavy-Duty Splined Belt / Ball Bearing Supported Shaft	
Rear Drum Propel Drive	Tension Activated V-Belt & Chain / Ball Bearing Idler	
Front Cartridge Drive	Tension Activated V-Belt / Ball Bearing Idler	
Speed Control	Engine Throttle / Adjustable Drive Lever Engagement	
Propel Speed	2.6 - 3.2 mph (4.2 - 5.2 km/h)	
Standard Reel Blade Cartridge	7 or 10-Blade - with Relief Grind	
Cutting Height Range	7-Blade: 0.23 - 1.2 in (6 - 30 mm)	
	10-Blade: 0.12 - 1.2 in (3 - 30 mm)	
Cutting Height Adjustment	Single Twist Knob with Height Indicator Label	
Rear Drum Roller - Configuration	2-Section Split Differential Function	
Rear Drum Roller - Material	Metal with Grooved Vulcanized Rubber Coating	
Unit Length - with Height Adjustment	40 - 42 in (102 - 107 cm)	
Unit Height - with Height Adjustment	38 - 40 in (97 - 102 cm)	
Unit Width	28 in (71 cm)	33 in (84 cm)
Effective Cutting Width	19.75 in (50.2 cm)	24.75 in (62.9 cm)
Standard Front Roller	Smooth or Split Grooved	
Unit Weight - 7-Blade Cartridge	Briggs - 183 lbs. (83 kg)	Honda - 218 lbs. (99 kg)
Smooth Front Roller, No Catcher	Honda - 187 lbs. (85 kg)	
Grass Catcher Capacity	20 gal (75 l)	24 gal (90 l)
Grass Catcher Dry Weight	11 lbs. (5 kg)	15 lbs. (7 kg)

LIMITED WARRANTY COVERAGE Mower Chassis / Frame: 2-years residential / 1-year commercial
 Briggs & Stratton XR550 / XR3.5 Engine: 2-years residential & commercial
 Honda GX120 / GX160 Engine: 3-years all applications